
### OOF Project Update

Rhonald Lua


#### Outline

- Program for performing an OOFstyle construction of a skeleton/mesh over a 3-D microstructure as scaffold
- Status of parallel/distributed OOF2
- Status of OOF on Windows



## -style meshing in






#### Goals

- Write a 3-D skeleton-modification engine, mimicking that in OOF2, that may form a basis of study and perhaps incorporated in a future version of OOF2 (i.e. OOF3).
- Build functioning mock-applications on top of the skeleton-modification routines to explore the feasibility of an OOF3.

#### Recall what OOF2 does

OOF2 fits an FE mesh on top of a microstructure derived from a micrograph or image:



http://www.ctcms.nist.gov/~rlua/oof2 Red-States/Blue-States image taken from Gastner, Shalizi, Newman


...such that each mesh element:

- 1. has a 'good' shape,
- 2. encloses a single type of material or color (i.e. homogeneous),
- 3. is much larger than a single pixel.

### OOF terminology primer

1. Skeleton - defines the geometry of the mesh.

Skeleton-modification - tools for modifying a skeleton so that it follows material boundaries.




(http://www.ctcms.nist.gov/~langer/oof2man/Section-Concepts-Skeleton.html)


Homogeneity energy:  $E_h = 1.0 - (Homogeneity index)$ 

### (continued) OOF terminology

3. Shape index -

11/06/2006





Shape energy:  $E_s = 1.0 - (Shape index)$ 

4. Effective element energy:  $E = \alpha E_h + (1-\alpha)E_s$ 


E is a measure of the desirability of an element.

It is used as an energy in skeleton annealing. Low E is generally good. Parameter 'alpha' ( $\alpha$ ) tunes the emphasis between homogeneity and shape.

# Calculation of indices in OOF3 mock-up

1. Homogeneity index - statistically sample the interior of the element for the dominant pixel.

Example: get a set of random points inside triangle.



Generate random points within parallelogram. Fold back points that fall outside the triangle

 $\verb|http://vcg.iei.pi.cnr.it/activities/geometry egraphics/point in tetra edro. \verb|htm|| \\$ 


2. Shape index - Ratio of the size of the inscribing sphere to the circumscribing sphere (times a normalizing factor).

Very small inscribed sphere!


# Design philosophy for OOF3 mock-up

- Extend the skeleton-modification methods of OOF2 into 3-D.
- Use as little run-time computer memory as possible (Memory that scales with the problem size). If you can compute it, then don't store it.
- · Simple, easy-to-use programming interface.
- Provide option to make skeleton compatible with periodic boundary conditions.

#### Skeleton data structure



# Class hierarchy for skeleton vertex




#### Microstructure format

Simple two-pixel color 3-D array. (Sufficient to define a machine part)

```
Input file
```

Graphics output



Use 1-D array of chars or bytes for storage: 00111110,00...

Each bit encodes a single pixel or phase


00111110000001111100001111111

# Skeleton-modification techniques

- Refinement break down tetrahedral elements into smaller tetrahedrons.
- Simulated annealing:
  - 1. Random (gaussian) nodal displacements.
  - 2. Nodal motion toward average neighbors' position.
  - 3. Nodal motion along an element edge towards microstructure interfaces (transition points).

### Refinement


Mark one or more element edges for bisection depending on element homogeneity or other user preference. Examples:



Edge bisection will induce the bisection of the element faces as well as those of neighboring elements.


### Tetrahedron Refinement: Java demo

(http://www.ctcms.nist.gov/~rlua/FE/refinery)



### Skeleton Refinement: Java demo

(http://www.ctcms.nist.gov/~rlua/FE/refinery/skeleton)



### Annealing

Monte Carlo molecular dynamics of the nodes Step 1: Pick nodes or vertices to move.


Step 2: Perform a trial move of each node.

Move possibilities:

- 1. Standard random (gaussian) nodal displacements
- 2. Smoothing move node towards the average position of its neighbors.
- 3. Snap-nodes move node along an edge towards the interface between two phases, called transition points.


Step 3: Accept or reject the move based on a boltzmann factor:  $exp(-\Delta E/T) > r$ 

# (continued) Annealing: Snap-nodes



#### Correlated Snap-nodes:

Example:








(http://www.ctcms.nist.gov/~langer/oof2man/RegisteredClass-SnapNodes.html)


(Present in OOF2, but not implemented yet in mock-ups.)

### OOF3 Demo WOOF-aC++/MFC/OpenGL

### create a microstructure:

Phase-0 (yellow) Phase-1 (cyan)








Phase-1 forms a donut (torus)

WOOF Messages and Controls	
2006 OOF Labs WOOF>Creating microstructure Reading microstructure data Pixel dimensions: 15 x 30 x 6 Physical dimensions: 15.000000 x 30.000000 x 6.000000done.	<u> </u>
Command line W00F>	More>>

### (demo continued) Create an initial skeleton









Because of z-periodic boundary condition, mesh topology is also a torus! (preserved after any skeleton modification) 20


### (demo continued)


Display wire-frame of elements that contain phase-1 as a dominant pixel





# (demo continued)Snap-nodes of initial skeleton







Homogeneity index increased by 0.01 and shape index decreased by 0.02. Skeleton changed little.


WOOF Messages and Controls	
Shape index: 0.754024 Iteration no. 9	▲
Acceptance rate: 0.342857	
Skeleton energy reduction rate: -0.005537 Homogeneity index: 0.888175	
Shape index: 0.751990	
MakeGLListSkeleton(GLLIST_SKEL_WIRES): 57 wire tets Number of tetrahedrons: 240	-
Number of vertices: 105	
Command line	
WOOF>	More
WOOF	

### (demo continued) Refine heterogeneous elements in skeleton


Homogeneity index increased considerably (up 0.06) but shape index went down (-0.11). Let us use anneal and smooth to try to remove the sharp edges that can injure an engineer!








# (demo continued) Standard Anneal







A modest change, shape index went up by 0.02.

WOOF Messages and Controls	
Skeleton energy reduction rate: -0.005538 Homogeneity index: 0.945480 Shape index: 0.665159 Iteration no. 9	_
Acceptance rate: 0.067114 Skeleton energy reduction rate: 0.008246 Homogeneity index: 0.946336 Shape index: 0.661985 MakeGLListSkeleton(GLLIST_SKEL_WIRES): 1040 wire tets	╛
Command line————————————————————————————————————	More>>

### (demo continued) Smoothing






Again, a modest change, shape index went up by 0.04.


Ac	peptance rate: 0.486577	_
Ho	eleton energy reduction rate: 0.003113 mogeneity index: 0.941028 ape index: 0.709357	
MakeGLListS	keleton(GLLIST_SKEL_WIRES): 390 wire tets rahedrons: 1040	₹
Command lin	ne	More>>

# (demo continued) Color-map of skeleton solids indicating element energy



microstructure (phase-1) + wires + solids

Cool colors (white, yellow) indicate badlyshaped elements




wires + solids

# Verifying the correctness of the skeleton

- Test that the tetrahedrons are non-singular, and that  $\Sigma V_{tets} = V_{box}$ .
- Congruence of skeleton Check that a face of a tetrahedron matches with exactly one other face in another element.
- Export the skeleton into abaqus (cae)

# Exported skeleton: OOF3 to Abaqus



#### Caveat!

This is a mock-up (albeit a working mock-up). Features in OOF2 that are missing in this mock-up:

- Scriptability be able to save/record your work and 'play' them back later. Key to automation.
- Defining materials and properties
- ·Image processing and skeleton manipulation
- ·FEM solver
- ·Parallel/distributed computing capability
- ·Portability e.g. for GUI interface code.
- ·Working with multiple microstructures, skeletons or mesh at the same time. Undo/Redo mechanism.
- ·And the list goes on...

Many of these features will carry over to OOF3 when OOF2 is used as a code-base.

# Options for Graphics and GUI toolkits


- Java AWT (Abstract Window Toolkit)
- VPython
- OpenGL + GTK. (Trivia: The dinosaurs in Jurassic Park and the T1000 in T2 were OpenGL applications.)
- VTK (Visualization ToolKit)
- · OpenDX

#### (Shifting gears...)

# Parallel/Distributed mode of OOF2

Process 1

Process O (front end)



Process 3

Process 2

### (continued) Parallel OOF2

#### TODO:


- •Combine the data and results into a single graphics output at the front-end.
- •Rigorous testing in a cluster. Professor R. Edwin Garcia has offered his computing resources at prometheus.ecn.purdue.edu (A Mac cluster).

#### OOF on Windows

Windows build using a native compiler (i.e. Visual C++)


Instead employ a Cygwin solution.
Cygwin (www.cygwin.com) is a tool for building Unix programs that will run on Windows.

### OOF2 on Cygwin



http://www.ctcms.nist.gov/~rlua/FE/win/oof2.html

### OOF1 on Cygwin



http://www.ctcms.nist.gov/~rlua/FE/win/oof1.html


### Acknowledgments

- Steve Langer, Andrew Reid (OOF mentors)
- Seung-Ill Haan (R. Lua learned the style of refining a tetrahedron from him.)


Visit: http://www.ctcms.nist.gov/~rlua/matcase Thank you!


### Supplementary material


Skeleton-modification using WOOF for a simple microstructure (cyallow3D)



#### Create an initial skeleton







Display skeleton wires and nodes (green).

### Snap-nodes

For the microstructure, display only the yellow pixels to see more clearly what went on...

